Global Ventures Australia

ABN 77 065 255 763

Eco-Core SVL (Solid Veneer Lumber) Faced Panel on White Birch Multiply DATA SHEET

SECTION 1 COMPANY IDENTIFICATION

| Company Name | Global Ventures Australia Pty Ltd |
|--------------|--|
| Address | Unit 13 / 22 Beaumont Road Mount Kuring Gai NSW 2080 Australia |
| Phone | + 61 2 9457 7171 |
| Website | www.ecocore.com.au |
| Email | enquiries@globalventures.com.au |

SECTION 2 PRODUCT

| Product Identification | |
|------------------------|--|
| Product Name | Eco-Core SVL (Solid Veneer Lumber) Faced Panel on White Birch Multiply |
| Timber Species | European Beech faces, European Birch core |
| Description | The Eco-Core SVL Faced Panel is made from approximately 3mm thick SVL laminated onto Eco-Core White Birch Multiply. It can be supplied laminated on one or both faces depending on the requirement. The thinly sliced SVL is stable when pressed on a substrate as there is less movement of the SVL faces. The advantage of using this product in some applications is that it can be supplied in thinner panels. |

SECTION 3 SIZE

| Panel Size | SINGLE SIDED |
|------------|--|
| | 2500mm x 1250mm x 25, 28, 34mm |
| | DOUBLE SIDED |
| | 2500MM x 1250mm x 14, 20, 26, 32, 38mm |

SECTION 4 CONSTRUCTION

| | The Eco-Core SVL Faced Panel is supplied raw, sanded to grit 60, long grain. It is a cladding material where |
|-----------------|--|
| | exposed edges may require a finishing strip, supplied separately. In the raw product small holes and cracks can |
| Construction | occur on the faces caused by open knots, cracks or similar. These holes and cracks are not classified as defects |
| 5011011 4011011 | and should be puttied with timber putty prior to fine sanding. It is not supplied to exact measurement, please allow |
| | for cutting or fine sanding to finished size. |
| | |

SECTION 5 COLOUR

| Colour | Light beige, light brown to medium brown. |
|--------|---|
| | |

SECTION 6 GLUE

| Glue | phenolic and moisture resistant polyurethane glues |
|------|--|

SECTION 7 DENSITY

| Density | Approximately 765 kg/m3 |
|-----------------------|-------------------------|
| SECTION 8 ENVIRONMENT | |
| SECTION 8 ENVIRONMENT | |

SECTION 9 MOISTURE

Environment

E0 Certified

| Moisture | Moisture content approximately 10-12% |
|----------|---------------------------------------|

Global Ventures Australia

ABN 77 065 255 763

SECTION 10 FIRE PROPERTIES

| OLOTION TO TIME THOSE ENTILO | |
|------------------------------|---|
| Fire Indices | Available as a separate document, please forward your enquiry to Global Ventures. |
| ECTION 11 APPLICATION | |
| | |
| Application | Large window/door frames, long span shelving, wall panelling, ceiling cladding, dividers/partitioning, bedroom/office doors, cabinetry, table/bench tops, furniture, joinery work, flooring and more. The appearance of an Eco-Core SVL SVL Faced Panel and SVL Flooring sample is indicative only. Color, grain and laminations can vary and are not classified as defects. Small samples do not always represent what a large surface will look like. |